



AXESS[®] PRO SERIES 3100

INDUSTRIAL SHUTTER OPENER

EVOLUTION HAS ARRIVED



AUTOMATING THE LARGEST OF DOORS WITH THE SMALLEST OF FUSS

The Axess[®] Pro Series 3100 range provides innovative features for the demanding world of industrial shutter and roll up door automation. With powerful inverter driven motor options, plus a scalable suite of logic and safety options, this combination of strength and smarts is an evolutionary step forward.

The Axess[®] Pro Series 3100 range is suitable for both roller shutters and roll up doors up to 36m² in size. These 240V units require only a standard power point for installation, but deliver 3-phase power, reliability and speed control through a custom designed inverter. Controlled either by a simple manual console, or the sophisticated logic control system with LCD screen, integrated time clock and TrioCode[™]128 technology, all units feature a Service Indicator to advise when a door service is due.



AT A GLANCE:

SECURE & RELIABLE TRANSMITTERS

The TrioCode[™]128 transmitter system ensures secure and reliable home access. It transmits on three frequencies to defeat radio interference, and uses a 128-bit encryption protocol (with trillions upon trillions of random codes*) for the ultimate in security.



*340,282,366,920,938,463,463,374,607,431,768,211,456 codes

POWERFUL MOTOR WITH SOFT START/STOP

A powerful 3-phase, inverter driven motor means this opener is reliable, quiet, offers soft start/stop operation, and backed by our 5-year warranty.

LOGIC CONTROLS WITH LCD SCREEN OPTION

The optional integrated logic control system with LCD screen provides scalable functionality, allowing the operation of the opener to be customised specifically to the site's needs.

QUIET, HEAVY DUTY GEARBOX

The high stepdown ratio gearing, immersed in a breatherless oil bath inside the cast aluminium gearbox, provides power and reliability with minimal noise.

SMART
SIMPLE
SECURE

AXESS[®] PRO SERIES 3100

INDUSTRIAL SHUTTER OPENERS

TECHNICAL SPECIFICATIONS

Axess [®] 3100 Series		
Power	Input Voltage	230-240V a.c. 1-phase
	Standby Power	2.8W
	Motor Type	Induction
	Motor Power	1.0 HP - 750W
	Controller Fuse	10A
	Rated Duty Cycle	60%
	Rated Door Area	1.0 HP - 36m ²
	Typical Travel Speed (shutter dependent)	Variable via inverter
Transmitter System	Receiver/Transmitter Frequency	Multi-frequency UHF FM (433.47, 433.92 & 434.37MHz)
	Coding System	Code hopping (Non-linear encryption algorithm)
	Code Combinations	3.4x10 ³⁸ code combinations (340,282,366,920,938,463,463,374,607,431,768,211,456 codes)
	Transmitter Type	TrioCode™128
	Transmitter Capacity (x 4-button registers)	511
Additional Features (with optional Logic Control Kit)	Courtesy Light	Output Available
	Safety Beam Compatibility	L2 Logics 3x Wireless Safety Beam/2-wire Safety Beam
	LCD Screen	Yes
	Warranty	5 year / 10,000 cycles

SAFETY & SECURITY FEATURES



Soft Start/Soft Stop
(inverter units only)



Door Profiling



POWER & MOUNTING SYSTEMS



3 Phase Motor with Inverter

OPERATING MODES & FEATURES



Service Indicator



Courtesy Light Output



Auto Close



Ventilation Mode



Vacation Mode



Time Clock



AUX Auxiliary Output



Wireless Safety Beam Ready



128
TrioCode™128

See our website for our icon glossary explanations.



Proudly Distributed by:

www.automatictechnology.com.au



www.facebook.com/ATA.Openers

**SMART
SIMPLE
SECURE**

©2020 Automatic Technology (Australia) Pty Ltd. All rights reserved. The Automatic Technology logos, "smart simple secure" wordage, feature icons, Axess[®] & TrioCode[™] are trademarks and registered trademarks of Automatic Technology (Australia) Pty Ltd. No part of this brochure may be reproduced without prior permission. In an ongoing commitment to product quality we reserve the right to change specification without notice. E&OE. 6-8 Fiveways Boulevard, Keysborough, Victoria, 3173. **Ph:** +61 (0) 3 9791 0200. **Fx:** +61 (0) 3 9791 0250. Printed Feb 2014. 204610 ATA Axess[®] Pro Series 3000.

For more information on this door opener and other Automatic Technology products please visit us online.

automatic
TECHNOLOGY